

# Mounting Medium

**TREVIGEN**<sup>®</sup> Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Revision Date: 04/24/2015 Date of issue: 04/24/2015

Version: 1.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Mounting Medium

**Product Code:** 4865-25

### 1.2. Intended Use of the Product

No use is specified

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Trevigen Inc.  
8405 Helgerman Court  
20877 Gaithersburg, MD 20877  
T 1-800-TREVIGEN

### 1.4. Emergency Telephone Number

**Emergency Number** : 301-216-2800

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### Classification (GHS-US)

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Repr. 2 H361  
STOT SE 3 H336  
STOT RE 2 H373  
Asp. Tox. 1 H304  
Aquatic Acute 2 H401  
Aquatic Chronic 3 H412

Full text of H-phrases: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

#### Hazard Pictograms (GHS-US)



#### Signal Word (GHS-US)

: Danger

#### Hazard Statements (GHS-US)

: H225 - Highly flammable liquid and vapor.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H336 - May cause drowsiness or dizziness.  
H361 - Suspected of damaging fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H401 - Toxic to aquatic life.  
H412 - Harmful to aquatic life with long lasting effects.

#### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 – IF SWALLOWED: Immediately call a poison center or doctor.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P312 - Call a poison center or doctor if you feel unwell.  
P331 - Do NOT induce vomiting.  
P362 - Take off contaminated clothing and wash before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, provincial, territorial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US) No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable

### 3.2. Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Toluene	(CAS No) 108-88-3	55	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Flush with plenty of water for at least 15 minutes. Seek medical advice if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do not induce vomiting. Rinse mouth. Immediately seek medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes skin irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

**Inhalation:** May cause drowsiness or dizziness.

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Skin Contact:** Causes skin irritation. Symptoms may include redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** May cause eye irritation.

**Ingestion:** May be fatal if swallowed and enters airways: Risk of serious damage to the lungs if swallowed (by subsequent aspiration). Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion. Reacts violently with incompatible materials to form other toxic and explosive materials.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Under fire conditions, hazardous fumes will be present and closed containers may rupture or explode.

**Firefighting Instructions:** Do not breathe fumes from fires or vapors from decomposition. Use water spray or fog for cooling exposed containers. Closed containers exposed to heat may explode. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow run-off from firefighting to enter drains or water sources.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons. Smoke.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe vapors, mist, or spray. Avoid all contact with skin, eyes, or clothing. Spillages of liquid product will create a fire hazard and form an explosive atmosphere. Use special care to avoid static electric charges. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ensure adequate ventilation.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container for disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Avoid contact with skin, eyes, and clothing. Use only non-sparking tools. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Ensure adequate ventilation. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, and lighting equipment. Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool, and well-ventilated place. Do not store near heat, flame, or other potential ignition sources. Do not store with oxidizers. Keep container closed when not in use. Ground all equipment containing this material. Keep/Store away from direct sunlight, extremely high or low temperatures, and incompatible materials.

**Incompatible Materials:** Strong oxidizers. Strong acids. Nitrogen oxides. Halogens.

#### 7.3. Specific End Use(s)

No use is specified.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Toluene (108-88-3)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	50 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA IDLH	US IDLH (ppm)	500 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	50 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (ppm)	20 ppm

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	60 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	100 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases/vapors may be released. Use explosion-proof equipment. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective goggles. Protective clothing. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Impermeable protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink, or smoke during use.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Not available
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- Explosion Data – Sensitivity to Mechanical Impact** : Not expected to present an explosion hazard due to mechanical impact  
**Explosion Data – Sensitivity to Static Discharge** : Not expected to present an explosion hazard due to static discharge

### SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion. Reacts violently with incompatible materials to form other toxic and explosive materials.  
**10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).  
**10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.  
**10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.  
**10.5. Incompatible Materials:** Strong oxidizers. Strong acids. Nitrogen oxides. Halogens.  
**10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons. Smoke.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness. May cause respiratory irritation

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Symptoms may include redness, pain, swelling, itching, burning, dryness, and dermatitis

**Symptoms/Injuries After Eye Contact:** May cause eye irritation

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways. Risk of serious damage to the lungs if swallowed (by subsequent aspiration). Ingestion is likely to be harmful or have adverse effects

**Chronic Symptoms:** Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure

#### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Toluene (108-88-3)	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
ATE US (vapors)	25.70 mg/l/4h

Toluene (108-88-3)	
IARC Group	3

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects. Toxic to aquatic life.

This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Toluene (108-88-3)	
LC50 Fish 1	15.22 (15.22 - 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 (5.46 - 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)

**12.2. Persistence and Degradability** Not available

**12.3. Bioaccumulative Potential**

<b>Toluene (108-88-3)</b>	
Log Pow	2.65

**12.4. Mobility in Soil** Not available

**12.5. Other Adverse Effects** Not available

## SECTION 13: DISPOSAL CONSIDERATIONS

**13.1. Waste treatment methods**

**Sewage Disposal Recommendations:** Do not empty into drains; dispose of this material and its container in a safe way.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial, and international regulations.

**Additional information:** Handle empty containers with care because residual vapors are flammable.

## SECTION 14: TRANSPORT INFORMATION

**14.1. In Accordance with DOT**

Proper Shipping Name : TOLUENE SOLUTION  
Hazard Class : 3  
Identification Number : UN1294  
Label Codes : 3  
Packing Group : II  
ERG Number : 130



**14.2. In Accordance with IMDG**

Proper Shipping Name : TOLUENE SOLUTION  
Hazard Class : 3  
Identification Number : UN1294  
Packing Group : II  
Label Codes : 3  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D



**14.3. In Accordance with IATA**

Proper Shipping Name : TOLUENE SOLUTION  
Packing Group : II  
Identification Number : UN1294  
Hazard Class : 3  
Label Codes : 3  
ERG Code (IATA) : 3L



**14.4. In Accordance with TDG**

Proper Shipping Name : TOLUENE SOLUTION  
Packing Group : II  
Hazard Class : 3  
Identification Number : UN1294  
Label Codes : 3



## SECTION 15: REGULATORY INFORMATION

**15.1. US Federal Regulations**

Mounting Medium	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard Immediate (acute) health hazard

# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations



<b>Toluene (108-88-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

### 15.2. US State Regulations

<b>Toluene (108-88-3)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b>	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.

<b>Toluene (108-88-3)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

### 15.3. Canadian Regulations

<b>Mounting Medium</b>	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
 	

<b>Toluene (108-88-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 04/24/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways



# Mounting Medium

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

### Party Responsible for the Preparation of This Document

Trevigen INC. 8405 Helgerman Court Gaithersburg, MD 20877 T: 301-216-2800

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2